



Federal Commander Digital System

Model SFCD10 and SFCD25

DIGITAL STATUS WARNING

- Up to 255 sites
- 10 person call list
- Conventional and trunking radio compatibility
- Optional Networking TCP/IP interface
- Send up to 20 e-mails for an alarm

The Federal Commander Digital System offers Emergency Management Directors and system operators complete, secure activation and status monitoring of any siren system, and consists of the SS2000D encoder, the Commander Software, and digital Siren Controllers. From siren activation to in-home alerting, this system is designed to provide your facility with complete alert and notification capability.

Federal Commander continues to evolve to meet the changing demands of customers throughout the world to provide a system unmatched in its features and ease of use. From controlling either one siren or more than 255, the system can expand to accommodate your changing community needs. By integrating Federal Commander with SmartMsg, now with a single mouse click, system operators can activate their outdoor warning sirens and send SmartMsg alerts to any personal device (cell phone, computer, pager, handheld radio, etc.) to notify specific people about the reason the sirens were activated with instructions on what to do. Federal Commander can also be used to activate sirens based on National Weather Service alerts with the use of EMTools software.

Over 20 different system alerts can be automatically configured and sent via email notification and SmartMsg notification to individuals or groups on their personal devices.

Digital Siren Controllers are available for both electronic sirens, speakers, and electromechanical sirens. These controllers come equipped with over-the-air programmability via secure digital technology.

HISTORICAL REFERENCE ONLY

FEDERAL COMMANDER SYSTEM (SFCD)



CCU MINIMUM REQUIREMENTS*

CCU Minimum Requirements*

- One Gigabyte or more of Random Access Memory (RAM).
- Two spare PCI BUS ports
- 160GB Hard Disk Drive or larger.
- SVGA Color Monitor and Controller.
(800 x 600 resolution minimum, 24 bit color recommended).
- CD RD-W Drive.
- 101-key Enhanced Keyboard.
- One Parallel Printer Port - LPT1
- One RS-232 Serial Port.
- Mouse pointing device.
- Dot Matrix Printer 24-Pin with Parallel Interface and cable.
- Phone Line (Required for voice call out and remote dial-in features).
- AC surge suppression device
- UPS (Optional equipment to provide CCU backup in case of primary AC failure).
- Window OS. XP, Vista, or 2003 Server.

*Sold separately or customer supplied

HOW TO ORDER

Contact our Federal Signal Sales Engineers to design a system that meets your specific requirements.

Considerations for system configuration:

- Specify model number:
(SFCD10) Windows application software for up to 10 sites
(SFCD25) Windows application software for up to 25 sites
- Specify Accessories:
(SFCD-W) Commander extended one-year warranty
(SFCDCLNT) TCP/IP client software (5 seats)
(SFCD-MODEM) 56K PCI Modem for phone dial out feature

NOTE: See EMTools and Codespear datasheets for ordering information.